



**PDMM-20  
GREENLEE**

- Kapacitivnost: do 100  $\mu$ F
- Napon: 1 mV - 450 V
- Struja: 0.1  $\mu$ A - 8A AC/DC
- Otpor: 0,001 k $\Omega$  - 6 M $\Omega$
- Fretkvencija: 10 Hz - 30 KHz
- Kategorija merenja: CAT II 450V, CAT III 300V
- BEZKONTAKTNO ispitivanje napona: 15V-450V



**DM200A  
GREENLEE**

- Kapacitivnost: 60.00nF - 3000 $\mu$ F
- Napon: 0.01mV - 1000V AC/DC
- Struja: 0.1  $\mu$ A - 8A AC/DC
- Otpor: 0,1 $\Omega$  - 60M $\Omega$
- Fretkvencija: 10 Hz - 50 kHz sinusni talas;  
5 Hz - 1 MHz kvadratni talas
- Kategorija merenja: CAT II 1000V, CAT III 600 V, CAT IV 300 V



**DM210A  
GREENLEE**

- Kapacitivnost: 60.00nF - 3000 $\mu$ F
- Napon: 0.01mV - 1000V AC/DC
- Struja: 0.1  $\mu$ A - 8A AC/DC
- Otpor: 0,1 $\Omega$  - 60M $\Omega$
- Fretkvencija: 10 Hz - 50 kHz sinusni talas;  
5 Hz - 1 MHz kvadratni talas
- Kategorija merenja: CAT II 1000V, CAT III 600 V, CAT IV 300 V
- Merenje temperature: -50 $^{\circ}$ C - 1000 $^{\circ}$ C
- Protok: 50Hz-400Hz



**DM510A  
GREENLEE**



- Kapacitivnost: 60.00nF - 3000 $\mu$ F
- Napon: 0.01 mV - 1000 V AC/DC
- Struja: 0.1  $\mu$ A - 8A AC/DC
- Otpor: 0.1 $\Omega$  - 60M $\Omega$
- Fretkvencija: 5 Hz - 1 MHz
- Kategorija merenja: CAT III 600V; CAT II 1000V; CAT IV 300 V
- Merenje temperature: -50 $^{\circ}$ C - 1000 $^{\circ}$ C
- Frequency pickup: 50Hz - 400Hz



**DM810A  
GREENLEE**



- Kapacitivnost: 0,01 nF - 25 mF
- Napon: 0,01 mV - 1000 V AC/DC
- Struja: 0.1μA - 10A AC/DC
- Otpor: 0.1Ω - 60MΩ
- Fretkvencija: 5 Hz – 1 MHz
- Kategorija merenja: CAT IV 1000 V



**DM820A  
GREENLEE**



- Kapacitivnost: 0,01 nF - 25 mF
- Napon: 0,01 mV - 1000 V AC/DC
- Struja: 0.1μA - 10A AC/DC
- Otpor: 0.1Ω - 60MΩ
- Fretkvencija: 5 Hz – 1 MHz
- Kategorija merenja: CAT IV 1000 V
- Merenje temperature: -50°C - 1000°C
- Bezkontaktna detekcija napona od 10 – 1000 V



**DM860A  
GREENLEE**



- Kapacitivnost: 50nF - 9999μF
- Napon: 500 mV - 1000 V AC/DC
- Struja: 500 μA - 10A AC/DC
- Otpor: 500Ω - 50MΩ
- Fretkvencija: 5 Hz - 200 kHz sinusni talas;  
5 Hz - 2 MHz kvadratni talas
- Kategorija merenja: CAT IV 1000 V
- Merenje temperature: -50°C - 1000°C
- Frequency pickup: 50Hz - 400Hz
- Bezkontaktna detekcija napona od 10 – 1000 V

- Kapacitivnost: 0 - 200μF
- Napon: 0 - 300 V AC/DC
- Otpor: 0 - 40MΩ
- Fretkvencija: 0 - 200 kHz
- Kategorija merenja: CAT III 300 V