



**CM-450  
GREENLEE**



- Displej: LCD 4000
- Napon: 0,01 - 600 V AC/DC
- Struja: 0,01 – 400 A AC
- Otpor: 0,1 k $\Omega$  - 40 M $\Omega$
- Otvor čeljusti: 26 mm(185 mm<sup>2</sup>)
- Kategorija merjenja: CAT III 600V



**CM-660  
GREENLEE**



- Displej: LCD 6000
- Napon: 0,1 - 600 V AC/DC
- Struja: 0,01 – 600 A AC
- Otpor: 0,1 k $\Omega$  - 60 K $\Omega$
- Kapacitivnost: do 2500  $\mu$ F
- Otvor čeljusti: 30 mm(240 mm<sup>2</sup>)
- Kategorija merjenja: CAT III 600V, CAT IV 300V
- Test kontinuiteta
- Bezkontaktna detekcija napona 10 - 600 V



**CM-860  
GREENLEE**



- Displej: LCD 6000
- Napon: 0,1 - 600 V AC/DC
- Struja: 0,01 – 600 A AC
- Otpor: 0,1 k $\Omega$  - 60 K $\Omega$
- Kapacitivnost: do 2500  $\mu$ F
- Otvor čeljusti: 30 mm(240 mm<sup>2</sup>)
- Kategorija merjenja: CAT III 600V, CAT IV 300V
- Test kontinuiteta
- Bezkontaktna detekcija napona 10 - 600 V



**CM-960  
GREENLEE**



- Displej: LCD 6000
- Napon: 0,1 - 600 V AC/DC
- Struja: 0,01 – 600 A AC/DC
- Otpor: 0,1 k $\Omega$  - 60 K $\Omega$
- Kapacitivnost: do 2500  $\mu$ F
- Frekvencija: 5 – 999 Hz
- Otvor čeljusti: 35 mm(300 mm<sup>2</sup>)
- Kategorija merjenja: CAT III 600V, CAT IV 300V
- Test kontinuiteta
- Bezkontaktna detekcija napona 10 - 600 V



**CM1360  
GREENLEE**



- Displej: LCD 6000
  - Napon: 0,1 - 1000 V AC
  - Struja: 0.01 – 1000 A AC/DC
  - Otpor: 0,1 k $\Omega$  - 60 K $\Omega$
  - Kapacitivnost: do 2500  $\mu$ F
  - Frekvencija: 5 – 999 Hz
  - Otvor čeljusti: 51 mm(400 mm<sup>2</sup>)
  - Kategorija merenja: CAT III 1000V, CAT IV 600V
  - Test kontinuiteta
  - Bezkontaktna detekcija napona 10 - 1000 V
- 



**CM-1560  
GREENLEE**



- Displej: LCD 6000
  - Napon: 0,1 - 1000 V AC/DC
  - Struja: 0.01 – 1000 A AC/DC
  - Otpor: 0,1 k $\Omega$  - 60 K $\Omega$
  - Kapacitivnost: do 2500  $\mu$ F
  - Frekvencija: 5 – 999 Hz
  - Otvor čeljusti: 51 mm(400 mm<sup>2</sup>)
  - Kategorija merenja: CAT III 1000V, CAT IV 600V
  - Test kontinuiteta
  - Bezkontaktna detekcija napona 10 - 1000 V
-