

K 50 Mehanička ručna presa sa izmenjivim umetcima



- Paralelno vođene čeljusti za presovanje
- Brza zamena matrice za presovanje bez podešavanja posebnim sistemom fiksiranja
- Tačno pozicioniranje matrica za presovanje zahvaljujući pinovima za lociranje kalupa
- Optimizovan prenos sile
- Sa čegrtaljkom za konstantno kontrolisane rezultate presovanja
- Ručka sa zaštitom od klizanja

Tehničke karakteristike	
Dužina	220mm
Težina	0,6 kg
Kataloška oznaka	K50
Oprema koja se posebno poručuje	
Metalni kofer MK55	
Izmenjive matrice za:	
Cu cevaste kablovske papučice, std. tip od 0,75 - 10mm ²	
Cu cevaste kablovske papučice, std. tip od 6 - 25mm ²	
Cu cevaste kablovske papučice, pun presek od 1,5 - 10mm ²	
Cu cevaste kablovske papučice, (DIN 46235 i DIN 46267 deo 1) od 6 - 25mm ²	
Terminali po DIN 46234, igličaste papučice po DIN 46230 i Cu papučice po DIN 46341 od 0,5-10mm ²	
Izolovani bezlemni terminali i konektori od 10-16mm ²	
Izolovane hilzne od 0,5-16mm ² od 0,5 - 50 mm ²	
Izolovane duple hilzne od 2 x 6 - 2 x 16 mm ²	
Izolovane buksne, jednostruko presovanje od 0,5 - 16 mm ²	
Izolovane buksne, dvostuko presovanje od 0,1 - 6 mm ²	
Neizolovane buksne od 0,25 - 6 mm ²	
BNC konektori za koaksijalne kablove RG 58, 59, 60 i 71	
Pin terminali od 0,1 - 4 mm ²	

Za više detalja o izmenjivim matricama pogledajte odeljak : [IZMENJIVE MATRICE](#)