

PK 60 ID Hidraulična glava za presovanje 10 - 240 mm²



- Veliki opseg presovanja zahvaljujući inovativnom 2-stepenom teleskopskom cilindru
- Ubodno presovanje, umetci nisu potrebni
- Zatvorena stezna glava sa brzoskidajućom spojkom, rotirajuća
- Za povezivanje na hidraulične pumpe sa radnim pritiskom od 700bar

Tehničke karakteristike	
Sila presovanja	30-60kN
Hod klipa	40,5mm
Opseg presovanja Cu	10-240mm ²
Opseg presovanja Al	50-240mm ²
Radni pritisak	max. 700bar
Dužina	249.5mm
Težina	pribl. 2.5kg
Kataloška oznaka	PK60ID
Isporuka obuhvata	kat. oznaka
Torba za nošenje	TT2
Odgovarajuće za:	
Cu cevaste kablovske papučiće i konektore std. tipa, od 10-240mm ²	 
Cu cevaste kablovske papučiće i konektore za fine licnaste provodnike, od 10-240mm ²	 
Bezlemni terminali (DIN 46234), konektori i pin terminali (DIN 46230 i DIN46341) od 10-240mm ²	 
Al kablovske papučiće i konektori od 50-240mm ²	 
Bimetalne kablovske papučiće i konektori od 50-240mm ²	 